



Origin™

Vented, Over-Molded Frame



Military Standard
MIL-PRF-31013
VO Ballistics



STANDARD	IMPACT SPEED	CALIBER / SIZE	PROJECTILE
ANSI Z87.1 + High Velocity	150 feet / second 45 meters / second	0.25 inch diameter steel ball (25 caliber)	
Mil-PRF-31013 VO Ballistic	640-660 feet / second 195 meters / second	0.15 inch diameter steel projectile (15 caliber)	



Vented, Over-Molded Frame
Provides extra fog control and comfort



Telescoping Temples
For a customized and comfortable fit

Replaceable Polycarbonate Lens
Provides impact resistance

Rubber Nosepiece
For all day comfort

Meets ANSI Z87.1 & VO Ballistics Standards and Provides 99.9% UVA/UVB Protection.

Imprinting Available

Origin™	
Part No.	Color
OR1-11	Clear A/F
OR1-21	Smoke A/F
OR1-41	Amber Anti-Fog
OR1-451	Coffee Anti-Fog
OR1-61	Silver Mirror A/F
OR1-91	I/O Anti-Fog

Origin™ Replacement Lens	
Part No.	Description
ORRL-11	Clear A/F
ORRL-21	Smoke A/F
ORRL-41	Amber Anti-Fog
ORRL-451	Coffee Anti-Fog
ORRL-61	Silver Mirror A/F
ORRL-91	I/O Anti-Fog

Packaging	
Unit	Qty
Box	12
Case	300

Up to 2 colors:
Temple and/or Lens
(Right, Left, or Both)



Michigan

Toll Free: 800-483-2462
Phone: 616-866-2220 / Fax: 616-866-3615

Nevada

Toll Free: 877-723-9378
Phone: 775-284-8295 / Fax: 775-284-8291

Tennessee

Toll Free: 877-723-4267
Phone: 901-388-7776 / Fax: 901-266-2558